

PENDANT CABLE

UL Type STOOW Cable/ CSA STOOW / 600V 105° / FT1



Construction

Conductors: Flexible Stranded Bare Copper Conductors
 Insulation: PVC
 Jacket: Black PVC, Yellow on request
 Color: Yellow, Blue, Brown, Orange, White, and Purple
 Strain Relief: A1/16" (7x7) Internal Galvanized Steel Messenger

Features

- Flexible construction
- Durable Oil Resistant Outer Jacket

Approvals

- UL STOOW 600V 105° C
- CSA STOOW 105° C
- FT1

Technical details

Temperature range: 105°
 AC Voltage Rating: 600 V

Application

For use in Hoist and Pendant applications. Rated for continuous use up to 105° C.

WITH INTERNAL STEEL MESSENGER

Part Number	N. of Cores	Conductor AWG	Conductor Stranding	Insulation Thickness Inch (mm)	Jacket Thickness Inch (mm)	OD Inch (mm)	Cable Wt lbs/Mft (kg/km)
62Y030150UL	3	16	65/34	0.032 (0.81)	0.065 (1.65)	0.514 (13.06)	100 (149)
62Y050150UL	5	16	65/34	0.032 (0.81)	0.085 (2.16)	0.554 (14.07)	173 (257)
62Y070150UL	7	16	65/34	0.032 (0.81)	0.085 (2.16)	0.592 (15.04)	185 (275)