

FESTOON CABLE CONNECTOR



Construction

Body Material: Aluminum (other materials available on request)
 Bushing Material: Neoprene
 Nut: Aluminum

Features & Specifications

-Indoor and outdoor locations
 -Termination with both mechanical & environmental integrity which minimizes the incidence of disconnector power
 - IP 54 and Nema 3/3R, IP 65 and Nema 4, IP 67 and Nema 6, IP 52 and Nema 12 (Aluminum)
 -Temperature -40° / 150° C (Aluminum)

Approvals

-UL
 -CSA
 -NEC
 -ROHS & WEE

Application

Specifically designed for flat cable, festoon application, heavy-duty.

Connector Part Number	Connector Dimension (Inch)	Cable Part Number	Cable Description
XR-RSF-3001	1" Aluminum .660x.240	67040250UL	Flat PVC 14G 4c
XR-RSF-3001	1" Aluminum .660x.240	67040400UL	Flat PVC 12G 4c
XR-RSF-3003	1" Aluminum .890x.290	67040600UL	Flat PVC 10G 4c
XR-RSF-4001	1-1/4" Aluminum 1.190x.350	67041000UL	Flat PVC 8G 4c
XR-RSF-6002	2" Aluminum 1.460x.450	67041600UL	Flat PVC 6G 4c
XR-RSF-6001	2" Aluminum 1.710x.500	67042500UL	Flat PVC 4G 4c
XR-RSF-6008	2" Aluminum 1.90x.540	67043500UL	Flat PVC 2G 4c
XR-RSF-4004	1-1/4" Aluminum 1.130x.220	67080150UL	Flat PVC 16G 8c
XR-RSF-4002	1-1/4" Aluminum 1.370x.250	67080250UL	Flat PVC 14G 8c
XR-RSF-4002	1-1/4" Aluminum 1.370x.250	67080400UL	Flat PVC 12G 8c
XR-RSF-6004	2" Aluminum 1.650x.220	67120150UL	Flat PVC 16G 12c
XR-RSF-7002	2-1/2" Aluminum 2.18x.300	67160150UL	Flat PVC 16G 16c
XR-RSF-5015	1-1/2" Aluminum 1.415x.265	673080150UL	Flat PVC 16G 8c SHD